


72FG


FEMMINA DIRITTA BSPP SV.60° BSPP STRAIGHT FEMALE 60° FLARE



part ref.	Hose ID		Thread T	Dimension (mm)			Weight Kg
	[in]	size		hex H	Cut-off C		
72FG0203	3/16"	03	1/8-28	14	16		0,019
72FG0403	3/16"	03	1/4-19	19	18		0,028
72FG0603	3/16"	03	3/8-19	22	20		0,051
72FG0204	1/4"	04	1/8-28	14	16		0,018
72FG0404	1/4"	04	1/4-19	19	18		0,031
72FG0604	1/4"	04	3/8-19	22	20		0,043
72FG0804	1/4"	04	1/2-14	27	22		0,069
72FG0405	5/16"	05	1/4-19	19	18		0,033
72FG0605	5/16"	05	3/8-19	22	20		0,040
72FG0805	5/16"	05	1/2-14	27	22		0,070
72FG0406	3/8"	06	1/4-19	19	18		0,037
72FG0606	3/8"	06	3/8-19	22	20		0,047
72FG0806	3/8"	06	1/2-14	27	22		0,072
72FG0608	1/2"	08	3/8-19	22	20		0,067
72FG0808	1/2"	08	1/2-14	27	23		0,078
72FG1008	1/2"	08	5/8-14	30	23		0,090
72FG1208	1/2"	08	3/4-14	32	22		0,113
72FG0810	5/8"	10	1/2-14	27	23		0,095
72FG1010	5/8"	10	5/8-14	30	22		0,095
72FG1210	5/8"	10	3/4-14	32	22		0,116
72FG1212	3/4"	12	3/4-14	32	23		0,132
72FG1612	3/4"	12	1-11	38	25		0,166
72FG1616	1"	16	1-11	38	26		0,222

72NG

FEMMINA 90° BSPP SV.60° BSPP 90° FEMALE 60° FLARE



part ref.	Hose ID		Thread T	Dimension (mm)				Weight Kg
	[in]	size		hex H	Cut-off C	Drop D		
72NG0203	3/16"	03	1/8-28	14	22	24	0,023	
72NG0403	3/16"	03	1/4-19	19	23	28	0,036	
72NG0404	1/4"	04	1/4-19	19	25	28	0,430	
72NG0604	1/4"	04	3/8-19	22	25	31	0,058	
72NG0605	5/16"	05	3/8-19	22	29	36	0,065	
72NG0606	3/8"	06	3/8-19	22	33	35	0,069	
72NG0806	3/8"	06	1/2-14	27	33	37	0,099	
72NG0608	1/2"	08	3/8-19	22	39	41	0,106	
72NG0808	1/2"	08	1/2-14	27	39	41	0,127	
72NG1008	1/2"	08	5/8-14	30	39	44	0,145	
72NG1208	1/2"	08	3/4-14	32	39	44	0,168	
72NG1010	5/8"	10	5/8-14	30	45	49	0,162	
72NG1210	5/8"	10	3/4-14	32	45	51	0,188	
72NG1212	3/4"	12	3/4-14	32	56	54	0,237	
72NG1612	3/4"	12	1-11	38	56	58	0,296	
72NG1616	1"	16	1-11	38	70	65	0,418	