


## 72MS


### MASCHIO METRICO SV.24° DKOS PESANTE METRIC MALE 24° FLARE S TYPE



part ref.	Hose ID		Thread	Dimension (mm)			Weight Kg
	[in]	size		hex H	Tube	Cut-off C	
72MS1603	3/16"	03	M16-1,5	17	8	26	0,025
72MS1604	1/4"	04	M16-1,5	17	8	27	0,032
72MS1804	1/4"	04	M18-1,5	19	10	27	0,039
72MS2004	1/4"	04	M20-1,5	22	12	29	0,047
72MS2005	5/16"	05	M20-1,5	22	12	29	0,054
72MS1806	3/8"	06	M18-1,5	22	10	27	0,044
72MS2006	3/8"	06	M20-1,5	22	12	29	0,052
72MS2206	3/8"	06	M22-1,5	22	14	31	0,064
72MS2406	3/8"	06	M24-1,5	24	16	31	0,070
72MS2408	1/2"	08	M24-1,5	24	16	32	0,078
72MS3010	5/8"	10	M30-2	30	20	34	0,127
72MS3012	3/4"	12	M30-2	30	20	35	0,137
72MS3612	3/4"	12	M36-2	36	25	38	0,194
72MS3616	1"	16	M36-2	36	25	39	0,252
72MS4216	1"	16	M42-2	46	30	42	0,338
72MS4220	1.1/4"	20	M42-2	46	30	43	0,390
72MS5220	1.1/4"	20	M52-2	55	38	50	0,497
72MS5224	1.1/2"	24	M52-2	55	38	50	0,632

## 72FS

### FEMMINA DIRITTA METRICA SV.24° DKOS METRIC STRAIGHT FEMALE 24° FLARE S TYPE



part ref.	Hose ID		Thread	Dimension (mm)			Weight Kg
	[in]	size		hex H	Tube	Cut-off C	
72FS1603	3/16"	03	M16-1,5	19	8	25	0,034
72FS1604	1/4"	04	M16-1,5	19	8	25	0,036
72FS1804	1/4"	04	M18-1,5	22	10	24	0,048
72FS1805	5/16"	05	M18-1,5	22	10	24	0,050
72FS2005	5/16"	05	M20-1,5	24	12	26	0,061
72FS1806	3/8"	06	M18-1,5	22	10	24	0,062
72FS2006	3/8"	06	M20-1,5	24	12	26	0,062
72FS2206	3/8"	06	M22-1,5	27	14	29	0,089
72FS2408	1/2"	08	M24-1,5	30	16	29	0,111
72FS3010	5/8"	10	M30-2	36	20	33	0,196
72FS3012	3/4"	12	M30-2	36	20	34	0,190
72FS3612	3/4"	12	M36-2	46	25	40	0,341
72FS3616	1"	16	M36-2	46	25	41	0,287
72FS4216	1"	16	M42-2	50	30	43	0,451
72FS5220	1.1/4"	20	M52-2	60	38	44	0,650
72FS5224	1.1/2"	24	M52-2	60	38	44	0,694